Penticton Forklift Training Course

Penticton Forklift Training Course - CSA and OSHA establish criteria for forklift safety training that meets existing regulations and standards. Anyone intending to use a forklift is needed to successfully complete safety training before utilizing any type of forklift. The accredited Forklift Operator Training Program is intended to provide those training with the information and practical skills to become an operator of a forklift.

There are forklift operation safety rules which should be followed pertaining to pre-shift checks, and regulations for lifting and loading.

Prior to a shift beginning, an inspection checklist has to be carried out and given to the Instructor or Supervisor. If whatever maintenance problem is discovered, the machinery should not be operated until the issue is addressed. To indicate the machinery is out of order, the keys should be removed from the ignition and a warning tag placed in a visible place.

Loading safety rules comprise checking the forklift nameplate's rating capacity and knowing if the weight of the load falls within capacity. The forklift forks should be in the downward position when the forklift is starting up. Bear in mind that there is a loss of approximately 100 pounds carrying capacity for every inch further away from the carriage that the load is carried.

To be able to safely lift a palletized load, drive the forklift to the pallet and halt with the fork three inches away from the load. Level the mast until it is at right angles to the load. Raise the forks to one inch under the slot on the pallet and drive forward. Afterward lift forks four inches. Tilt back the load to secure it for moving. Drive the lift in reverse if the load obscures frontal vision. Check behind and honk to warn other staff. Never allow forks to drag on the ground.

Forklift loads must be loaded in such a way that they are secure and do not create a danger to other people or objects. Restraining loads is needed for materials which may shift during transport and destabilize the forklift.

To prevent the movement of drums, drums could be strapped together to decrease movement. Forklift operators must drive slowly when moving liquids, to decrease instability in the forklift.